

M260

Ultra Durable Wax/Resin



Product Description

This ribbon print on a broad range of label stocks, providing abrasion resistance and print sensitivity at speeds up to 12 IPS . It is perfect for printing long lasting images on coated tags, uncoated tags, and glossy print media. Designed with our specially formulated backcoat technology for printhead protection, this ribbon also contains exclusive anti-static properties for easier handling and extra printhead protection.

Recommended Applications



Compliance



Food Beverage



Health Beauty



Inventory Logistics



Outdoor



Pharmaceutical



Retail

Product Features

Abrasion Resistant	✓
Halogen-free	✓
High-density	✓
High-speed	✓
Printhead Protection	✓
Proprietary Backcoat	✓
Reduced Print Energy Use	✓
Solvent Resistant	✓

Recommended Substrates

Paper	Coated Paper
	Uncoated Paper
Economy Synthetics	Kimdura
	Polyart
	Polyethylene
	Polyolefin
	Polypropylene
	Synthetic Paper
	Valeron

Ribbon Properties

Ink	Wax/Resin
Color	Black
Base Film Thickness	4.0 ± 0.4μ
Ink Thickness	3.5 ± 0.5μ
Total Thickness	7.5 ± 0.9μ
Ink Transfer Temperature	Uncoated Tag 79°C (174°F)

Compliant with

REACH, RoHS, FDA (indirect food contact)

Dai Nippon Printing Co., Ltd.

Imaging Communications Operations
1-14-1, Ichigaya-Tamachi, Shinjuku-ku, Tokyo 162-8001, Japan
<http://www.dnp.co.jp/imaging/tr/jp/>

TEL +81-3-6735-6226

FAX +81-3-6735-6232