

## R300

General Purpose Resin



### Product Description

With extensive label adaptability and high print speed capability, this resin is the most diverse of its kind. It outperforms the competition in abrasion and solvent resistance, uses less print energy, and is designed with our standard anti-static and backcoat properties to protect printheads and extend printheads life.

### Recommended Applications



### Recommended Substrates

Economy Synthetics	Polyester
	Polyethylene
	Polyolefin
Specialty Materials	Polypropylene
	Vinyl

### Product Features

Abrasion Resistant	✓
Anti-static	✓
High-density	✓
High-speed	✓
Printhead Protection	✓
Proprietary Backcoat	✓
Reduced Print Energy Use	✓
Solvent Resistant	✓

### Ribbon Properties

Ink	Resin
Color	Black
Base Film Thickness	4.5 ± 0.4µ
Ink Thickness	1.3 ± 0.4µ
Total Thickness	5.8 ± 0.8µ

### Compliant with

REACH, RoHS, FDA (indirect food contact)
--

### Labeling References

UL, cUL
<ul style="list-style-type: none"> <li>■ 3M file # PGJ12.MH16411, PGJ12.MH18072, PGJ12.MH45276</li> <li>■ Avery file # PGJ18.MH17205, PGJ18.MH20558, PGJ18.MH20580, PGJ18.MH26285, PGJ18.MH27538</li> <li>■ FLEXcon file # PGJ12.MH16635</li> <li>■ MACTac® file # PGJ12.MH2676</li> <li>■ UPM Raflatac file # PGJ12.MH26760</li> </ul>
BS5609(GHS label)
FLEXcon DRUMcal 51932, MACTac FCD6914

### Dai Nippon Printing Co., Ltd.

Imaging Communications Operations  
 1-14-1, Ichigaya-Tamachi, Shinjuku-ku, Tokyo 162-8001, Japan TEL +81-3-6735-6226 FAX +81-3-6735-6232  
<http://www.dnp.co.jp/imaging/tr/jp/>